


Sportslighter

ITEM NUMBER	ITEM DESCRIPTION	1-4 UNITS EACH	5-9 UNITS EACH	10+ UNITS EACH
SP50-M1500Q-BZ-L-AR19-SPGL-CB19	Sportslighter 50 – 1500W Metal Halide – Quad-Tap Magnetic Ballast – Bronze – with Lamp – AR19 Standard Reflector – Glass with Clamp Band	\$355	\$341	#326
SP50-M1000Q-BZ-L-AR19-SPGL-CB19	Sportslighter 50 – 1000W Metal Halide – Quad-Tap Magnetic Ballast – Bronze – with Lamp – AR19 Standard Reflector – Glass with Clamp Band	\$254	\$244	\$233
SP50AR19-LB	Lamp Brace	2.50	2.50	2.50
SP50-HY	Mounting Yoke with Handle	14.65	14.65	14.65
SP50-PT	Pole Top Mount	24.50	24.50	24.50

NOTES:

- Freight: Prepaid and Charge. Typically FOB from either Cerritos, CA or Vancouver, WA. (We also ship from warehouses in Walden, NY and Tampa, FL.)

SP50 SERIES: Sportslighter > H.I.D.

MAXIMUM WATTAGE	APPLICATIONS	Click Photo to Enlarge.	BALLAST BOX DIMENSIONS
High Pressure Sodium (H): 1000W Metal Halide (M): 1500W Pulse Start Metal Halide (P): 1000W	- Stadium - -Large Area- -Security-		Width: 9 inches Height: 5-3/4 inches Depth: 13 inches

DESCRIPTION: These multi-purpose fixtures are ideal for stadium and large area lighting. Choose from four different reflectors. They are available in High Pressure Sodium and Metal Halide in high wattages. Includes Flat Tempered Glass Lens with Silicone Gasket and Standard Aluminum Clamp Band. We offer numerous mounting options for locating them on the ground, a wall, a roof, or a pole.

MODEL CODE (Partial) See Legend below to complete code.	LAMP & BALLAST DATA							VOLTS	BALLAST TYPE
	LAMP TYPE	LAMP BASE	WATTS	INITIAL LUMENS*	LAMP HOURS*	CRI*			
SP50-H400-Q	High Pressure Sodium (H)	Mogul	400W	50,000	24,000+	22	Quad-Tap: 120V, 208V, 240V, 277V. (Q)	Magnetic CWA	
SP50-H1000-Q			1000W	125,000					
SP50-M1000-Q	Metal Halide (M)		1000W	110,000	10,000	65			
SP50-M1500-Q			1500W	155,000	3,000				
SP50-P400-Q	Pulse Start Metal Halide (P)		400W	36,000					
SP50-P1000-Q			1000W	110,000V 107,800H	15,000V 9,000H				

*Initial Lumens, Lamp Hours and CRI (Color Rendering Index) may vary from one lamp manufacturer to another. Also, this data is for the most commonly used types of these lamps. Some lamp manufacturers also offer H.I.D. lamps in versions that are more environmentally friendly, have improved CRI, or have coated envelopes. See our [Industry Links](#) page to find the websites of major lamp manufacturers for detailed information.

SPECIFICATIONS (Click Links for details.)

SAFETY LISTING	CSA Listed as Suitable for Wet Locations.
BALLAST BOX	Die Cast Aluminum with Chromate Coating . Stamped Aluminum Cover with Silicone Gasket.
LAMP HOUSING	Die Cast Aluminum with Chromate Coating. Adjustable aim.
BALLAST BOX & LAMP HOUSING FINISH	Textured Bronze Polyester Powder Paint .
LENS	Clear flat tempered glass.
LAMPHOLDER	Porcelain 5KV pulse rated mogul base with nickel-plated screw shell.
LAMP	Optional.
REFLECTOR CHOICES	Spun Anodized Aluminum. Choice of I.E.S. Type 3, Type 4/5 or Type 6 light distribution. Corresponding Reflector codes are AR3, AR4/5, or AR6.
MOUNTING CHOICES	- Pole Top Mount (SP50-PT) - Yoke (SP50-Y)
OTHER ACCESSORIES	- Internal Lamp Brace for AR19 Reflector (SP50-AR19-LB) - Glare Shield for AR19 Reflector (SP50-AR19-GS)
PHOTOMETRICS	Selected Models available via e-mail in .pdf format and/or .ies format. Contact us with your request.
WAREHOUSES	Tampa, FL / Cerritos, CA / Walden, NY.

SP50 SERIES > Accessories



SP50-AR19 Standard Reflector

SPECIFICATIONS: 19" Diameter Spun Anodized Aluminum.
1.5mm Thick.

BENEFITS: Provides standard light distribution.

[Click Photos to Enlarge.](#)



SP50-AR3 Reflector

SPECIFICATIONS: 19" Diameter Spun Anodized Aluminum.
1.5mm Thick. Shiny finish.

BENEFITS: Provides light distribution Type 3.

[Click Photos to Enlarge.](#)



SP50-AR4/5 Reflector (Shown with Clamp Band & Glass)

SPECIFICATIONS: 19" Diameter Spun Anodized Aluminum.
1.5mm Thick. Semi-gloss finish.

BENEFITS: Provides light distribution Type 4/5 depending on socket bracket mounting position.

[Click Photos to Enlarge.](#)




SP50-AR6 Reflector (Shown with Clamp Band & Glass)

SPECIFICATIONS: 19" Diameter Spun Anodized Aluminum.
1.5mm Thick. Matte finish.

BENEFITS: Provides light distribution Type 6.

[Click Photos to Enlarge.](#)



SPGL-CB19 Flat Glass & Clamp Band

SPECIFICATIONS: Tempered flat clear glass lens with standard aluminum clamp band.
For SP50-AR19 Standard Reflector.

BENEFITS: Keeps weather out of reflector.

[Click Photos to Enlarge.](#)



SPGL-CBEZ19 Clamp Band

SPECIFICATIONS: Has E-Z on-off latching mechanism with locking tab for instant installation.
Fits SP50-AR19 Standard Reflector.

BENEFITS: No tools needed.

[Click Photos to Enlarge.](#)



SPGL22 & SPGL23 Flat Glass

SPECIFICATIONS: Tempered flat clear glass lens.

BENEFITS: SPGL22 fits SP50-AR4/5 & SP50-AR6 Reflectors.
SPGL23 fits SP50-AR3 Reflectors. Keeps weather out of reflectors.

[Click Photos to Enlarge.](#)



SP50-AR19LB Internal Lamp Brace

SPECIFICATIONS: Fits inside reflector.

BENEFITS: Stabilizes lamp. Reduces vibration.

[Click Photos to Enlarge.](#)

SP50-AR19GS Glare Shield



SPECIFICATIONS: Fits SP50-AR19 standard reflector. Includes mounting screws.

BENEFITS: Provides partial cutoff for glare control.

[Click Photos to Enlarge.](#)




SP50-PT Pole-Top Mount

SPECIFICATIONS: Textured Bronze Finish. Includes hardware.

BENEFITS: Allows fixture to sit atop a pole and be aimed.

[Click Photos to Enlarge.](#)



SP50-HY Handle Yoke Mount

SPECIFICATIONS: Heavy duty stamped yoke with mounting holes. Includes "handles" for aiming without tools.

BENEFITS: Provides method of attaching fixture to a flat surface with screws/bolts. Also provides aiming adjustment.